

AUTHOR INDEX

- Anzai, J., 115
- Beebe, K. R., 223
- Bergveld, P., 59, 179, 313
- Beuhler, A. J., 1
- Biermann, M., 277
- Bott, B., 19, 27
- Bousse, L. J., 179
- Bryant, M. D., 95, 105
- Carey, W. P., 223
- Carlson, E., 345
- Choi, S.-Y., 353
- Dahl, B., 345
- Dong-Bai Ye, 157
- Egashira, M., 147
- Esashi, M., 353
- Evans, N. J., 165
- Fürlinger, E., 73
- Geeraedts, H. J. M., 179
- Geladj, P., 223
- Guldan, A., 271
- Hanneborg, A., 345
- Hansen, T.-E., 345
- Heasell, E. L., 213
- Hetrick, R. E., 363
- Holwech, O., 345
- Hrubčín, L., 271
- Ihokura, K., 133
- Ikeuchi, K., 125
- Jones, T. A., 19, 27
- Kaiser, W. J., 363
- Kawamura, K., 157
- Kawana, Y., 373
- Kawasumi, S., 147
- Kayser, P., 323
- Keltie, R. F., 95
- Kimura, J., 373
- Ko, W. H., 333
- Kobayashi, T., 235
- Koudelka, M., 249
- Kowalski, B. R., 223
- Kuriyama, T., 373
- Kurobe, T., 301
- Lange, E., 39
- Launay, J. C., 323
- Lewis, E. R., 9
- Lian, W. J., 259
- Logothetis, E. M., 363
- Lucat, C., 323
- Matsuo, T., 115, 353
- Menil, F., 323
- Middelhoek, S., 259
- Misra, D., 213
- Müller, R., 39
- Nakajima, H., 115
- Offenbacher, H., 73, 85
- Ogita, M., 157
- Ohlckers, P. A., 345
- Ohsuga, M., 287
- Ohta, Y., 301
- Ohyama, Y., 287
- Osa, T., 115
- Oyabu, T., 301
- Petty, M. C., 165
- Petty-Weeks, W., 1
- Polak, A. J., 1
- Portier, J., 323
- Regtien, P. P. L., 199
- Roberts, G. G., 165
- Sadaoka, Y., 125
- Sakai, Y., 125
- Sánchez, E., 223
- Sprenkels, A. J., 59
- Sunahara, S., 133
- Takahashi, K., 49
- Takahashi, K., 353
- Tanguy, B., 323
- Vassell, W. C., 363
- Viswanathan, T. R., 213
- Voorthuyzen, J. A., 59, 313
- Wlodarski, W., 313
- Wolfbeis, O. S., 73, 85
- Wolffenbuttel, R. F., 199
- Wu, Q.-H., 333
- Wu, X.-P., 333
- Yamamoto, T., 157
- Yasunaga, S., 133
- Yoshida, Y., 147

SUBJECT INDEX

- Air-fuel ratios
 - study on oxygen-biased wide range air-fuel ratio sensor for rich and lean, 287
- Annular transmission
 - surface-barrier detector, 271
- Biological sensors, 9
- Biosensor
 - integrated SOS/FET multi-, 373
- Chemometric analysis
 - of multisensor arrays, 223
- 'Clark-type' oxygen sensor
 - performance characteristics of planar, 249
- Colour sensing
 - novel approach to solid-state, 199
- Consumer electronics
 - and home appliances in Japan, solid-state sensors and applications in, 235
- Copolymers
 - humidity sensors composed of grafted, 125
- Crown ether compounds
 - parylene-gate ISFET and chemical modification of its surface with, 115
- Dynamic performance
 - of practical piezoelectric actuator, characterization of linear and non-linear,
 - measurements, 95
 - theory, 105
- Elastic trunnion
 - as three-dimensional force and torque transducer, 277
- Electret air-gap field-effect structure
 - for sensor applications, théoretical analysis of, 59
- Electrical conductivity changes
 - gas-induced, in metal phthalocyanines, 27
- Electrodes
 - properties of Ag/AgCl, fabricated with IC-compatible technologies, 179
- Etching
 - of silicon, study of deep, using ethylenediamine-pyrocatechol-water, 333
- Ethylenediamine-pyrocatechol-water
 - study on deep etching of silicon using, 333
- Flip-flop sensors
 - new class of silicon sensors, 259
- Fluorescence optical sensors
 - for continuous determination of near-neutral pH values, 73
- Fluorescence sensor
 - for monitoring ionic strength and physiological pH values, 85
- Gas analysis
 - multidimensional sensor for, 39
- Gas leaks
 - oxide gas sensor and countermeasure system against accidental, 301
- Gas sensing characteristics
 - of tin oxide whiskers, 147
- Gas sensor(s)
 - high-sensitivity sensor for measurement of combustible gas mixtures, 363
 - oxide, and countermeasure system against accidental gas leaks, 301
 - SnO₂ ceramic-type semiconductor, effects of tetraethyl orthosilicate binder on characteristics of, 133
- Hazardous atmospheres
 - use of multisensor systems in monitoring, 19
- Humidity sensor
 - composed of grafted copolymers, 125
- Hydrogen sensing
 - applications of novel proton-conducting polymers to, 1
- Hydrogen sensor(s)
 - MISFET, stabilization of, 353
 - Pd-gate MOS, interface state effects in, 165
- Hydrogen-switching sensor
 - integrated, with Pd-Si tunnel MIS structure, 157

- IC-compatible technologies
 - properties of Ag/AgCl electrodes fabricated with IC-compatible technologies, 179
- Interface state effects
 - in Pd-gate MOS hydrogen sensors, 165
- Ionic strength
 - fluorescence sensor for monitoring, and physiological pH values, 85
- ISFET
 - parylene-gate, and chemical modification of its surface with crown ether compounds, 115
- Magnetic field sensor
 - novel high gain MOS, 213
- MBE/MOCVD technology
 - tailor-made sensing materials by, 49
- Metal phthalocyanines
 - gas-induced electrical conductivity changes in, 27
- MIS structure
 - integrated hydrogen-switching sensor with Pd-Si tunnel, 157
- MISFET hydrogen sensors
 - stabilization of, 353
- MOS hydrogen sensors
 - interface state effects in Pd-gate, 165
- MOS magnetic field sensor
 - novel high gain, 213
- MOS transistors
 - threshold voltage variations in N-channel, and MOSFET-based sensors due to optical radiation, 313
- MOSFET-based sensors
 - threshold voltage variations in N-channel MOS transistors and, due to optical radiation, 313
- Multidimensional sensor
 - for gas analysis, 39
- Multisensor arrays
 - chemometric analysis of, 223
- Multisensor systems
 - use of, in monitoring hazardous atmospheres, 19
- Optical radiation
 - threshold voltage variations in N-channel MOS transistors and MOSFET-based sensors due to, 313
- Optical sensors
 - fluorescence, for continuous determination of near-neutral pH values, 73
- Oxide gas sensor
 - and countermeasure system against accidental gas leaks, 301
- Oxygen
 - study on oxygen-biased wide range air-fuel ratio sensor for rich and lean air-fuel ratios, 287
- Oxygen sensor
 - planar 'Clark-type', performance characteristics of, 249
- Palladium
 - integrated hydrogen-switching sensor with Pd-Si tunnel MIS structure, 157
 - Pd-gate MOS hydrogen sensors, interface state effects in, 165
- Parylene-gate ISFET
 - and chemical modification of its surface with crown ether compounds, 115
- pH values
 - fluorescence optical sensors for continuous determination of near-neutral, 73
 - fluorescence sensor for monitoring ionic strength and physiological, 85
- Phthalocyanines
 - gas-induced electrical conductivity changes in metal, 27
- Piezoelectric actuator
 - characterization of linear and non-linear dynamic performance of practical, measurements, 95 theory, 105
- Polymers
 - applications of novel proton-conducting, to hydrogen sensing, 1
- Pressure sensor
 - integrated capacitive, with frequency-modulated output, 345
- Proton-conducting polymers
 - applications of novel, to hydrogen sensing, 1
- Sensing devices
 - for sodium vapour detection, 323
- Sensing materials
 - tailor-made, by MBE/MOCVD technology, 49
- Sensor(s)
 - biological, 9
 - flip-flop, new class of silicon, 259
 - fluorescence, for monitoring ionic strength and physiological pH values, 85

- fluorescence optical, for continuous determination of near-neutral pH values, 73
- gas, effects of tetraethyl orthosilicate binder on characteristics of SnO_2 ceramic-type semiconductor, 133
- novel high gain MOS magnetic field, 213
- high-sensitivity, for measurement of combustible gas mixtures, 363
- humidity, composed of grafted copolymers, 125
- integrated capacitive pressure, with frequency-modulated output, 345
- integrated hydrogen-switching, with Pd-Si tunnel MIS structure, 157
- MISFET hydrogen, stabilization of, 353
- MOSFET-based, threshold voltage variations in N-channel MOS transistors and, due to optical radiation, 313
- multidimensional, for gas analysis, 39
- oxide gas, and countermeasure system against accidental gas leaks, 301
- oxygen-biased wide range air-fuel ratio, for rich and lean air-fuel ratios, 287
- Pd-gate MOS hydrogen, interface state effects in, 165
- planar 'Clark-type' oxygen, performance characteristics of, 249
- solid-state, and applications in consumer electronics and home appliances in Japan, 235
- Sensor applications
 - theoretical analysis of electret air-gap field-effect structure for, 59
- Silicon
 - integrated hydrogen-switching sensor with Pd-Si tunnel MIS structure, 157
 - study on deep etching of, using ethylenediamine-pyrocatechol-water, 333
- Silicon sensors
 - flip-flop sensors, new class of, 259
- Silver
 - properties of Ag/AgCl electrodes fabricated with IC-compatible technologies, 179
- Sodium vapour detection
 - sensing devices for, 323
- Solid-state sensors
 - and applications in consumer electronics and home appliances in Japan, 235
- SOS/FET multi-biosensor
 - integrated, 373
- Surface-barrier detector
 - annular transmission, 271
- Tetraethyl orthosilicate binder
 - effects of, on characteristics of SnO_2 ceramic-type semiconductor gas sensor, 133
- Tin dioxide
 - effects of tetraethyl orthosilicate binder on characteristics of SnO_2 ceramic-type semiconductor gas sensor, 133
- Tin oxide whiskers
 - gas sensing characteristics of, 147
- Transducer
 - elastic trunnion as three-dimensional force and torque, 277
- Voltage variations
 - threshold, in N-channel MOS transistors and MOSFET-based sensors due to optical radiation, 313